CITY OF SUGAR LAND

BACKFLOW PREVENTION ASSEMBLY
CERTIFIED TEST REPORT

NAME OF PROPERTY:_____

PROPERTY ADDRESS:_____

SUBMIT REPORT TO:_____CITY OF SUGAR LAND, 111 GILLINGHAM LANE, SUGAR LAND, TX 77478

IF THE BACKFLOW PREVENTER PROTECTS A CROSS CONNECTION WHICH IS A HEALTH HAZARD AS DEFINED IN TEXAS ADMINISTRATIVE CODE (TAC) 290.47(i) AND THE BACKFLOW PREVENTER FAILS, THE TESTER IS REQUIRED TO NOTIFY THE CITY IMMEDIATELY AT 281-275-2450.
THE CERTIFIED TESTER SHALL ENSURE THE TESTER'S SIGNED ORIGINAL REPORT, PROOFS OF CURRENT TCEQ-ISSUED BPAT LICENSE AND CURRENT GAUGE CALIBRATION CHECK ARE PROVIDED TO THE WATER PURVEYOR WITHIN TEN BUSINESS DAYS OF TESTING.

THE BACKFLOW PREVENTION ASSEMBLY DETAILED HEREON HAS BEEN TESTED AND MAINTAINED AS REQUIRED BY TAC CHAPTER 290 RULES AND REGULATIONS FOR PUBLIC WATER SYSTEMS AND THE CITY'S ADOPTED PLUMBING CODE, AND IS CERTIFIED TO COMPLY WITH THE REQUIREMENTS.

TYPE OF ASSEMBLY

☐ REDUCED PRESSURE PRINCIPLE (RP)

☐ PRESSURE VACUUM BREAKER (PVB)

☐ DOUBLE CHECK VALVE (DCV)

☐ SPILL-RESISTANT PRESSURE VACUUM BREAKER (SVB)

MANUFACTURER:_____MODEL#:_____SIZE:_____SERIAL NUMBER:_____

METER #:_____DATE INSTALLED:_____

LOCATED AT:_____

	REDUCED PRESSURE PRINCIPLE ASSEMBLY			PRESSURE VACUUM BREAKER & SVB	
	DOUBLE CHECK VALVE ASSEMBLY		RELIEF VALVE	AIR INLET	CHECK VALVE
	CHECK VALVE #1	CHECK VALVE #2			
INITIAL TEST **Passed**	D.C. CLOSED TIGHT ☐ RP_____PSID LEAKED ☐	CLOSED TIGHT ☐ _____PSID LEAKED ☐	OPENED AT _____PSID DID NOT OPEN ☐	OPENED AT _____PSID DID NOT OPEN ☐	HELD AT _____PSID LEAKED ☐
REPAIRS AND MATERIALS USED					
FINAL TEST	CLOSED TIGHT ☐ RP_____PSID	CLOSED TIGHT ☐ RP_____PSID	OPENED AT _____PSID	OPENED AT _____PSID	HELD AT _____PSID

TEST GUAGE USED:_____ **(TESTED Annually)**

REMARKS:_____

_____

THE ABOVE IS CERTIFIED TO BE TRUE AT THE TIME OF TESTING.

CT's FIRM NAME:_____ **CERTIFIED TESTER NAME:** _____
(PLEASE PRINT)

FIRM ADDRESS:_____ **CERTIFIED TESTER SIGNATURE:**_____

_____ **TEST DATE:** _____

FIRM PHONE #:_____ ***CCC WITNESS:*** _____

*** TEST REPORTS MUST BE KEPT FOR AT LEAST THREE YEARS.**
TESTING IS REQUIRED UPON INSTALLATION, REPAIR, OR RELOCATION.
**** USE ONLY MANUFACTURERS' REPLACEMENT PARTS.**